LINKSYS® by Cisco



All-In-One Convenience

Enjoy fast wireless connectivity for your home or office. The Wireless-N Home ADSL2+ Modem Router has a built-in high-speed ADSL2+ Modem for a fast, "Always On" connection to the Internet. Wireless connections use Wireless-N technology for fast data transfers, and the four built-in 10/100 Ethernet ports supply high-speed connections to your wired devices.

Step up to the speed of Wireless-N

Easily create an around-the-home wireless network experience. Wireless-N technology allows your whole family to share one broadband Internet connection. Great for wireless printing and sharing files. Get best results when connecting to other Wireless-N devices, but also works great with Wireless-G and -B equipment.

Connection Versatility

Keep your digital files in one place, and share them from any computer on your network. Four built-in 10/100 Ethernet ports make it easy to connect additional wired computers, storage, printers, and other wired devices to your network.

Advanced Security

Advanced wireless security and SPI firewall protection helps safeguard your home network and computers from most Internet attacks.

DATASHEET

Cisco is the worldwide leader in wireless networking

Step up to the speed of Wireless-N

Connect and share a high-speed ADSL line

Easy to install on a Windows PC or Mac with Cisco Setup Wizard



Wireless-N Home ADSL2+ Modem Router

Model: WAG120N (EN)

Features

- ADSL modem router with Multi-Mode support:
 - ADSL T1.413 Issue 2, G. 992.1 (g.dmt), G.992.2 (G.Lite)
 - ADSL 2 G.992.3, G.992.3
 Annex L , G.992.3 Annex M
 - ADSL 2+ G.992.5, G.992.5
 Annex M
 - DTAG U-R2 for Annex B ADSL over ISDN
- · Wall mountable
- Industrial-strength wireless encryption WPA2[™] to ensure security
- Double the speed of G when used with Wi-Fi Certified Draft 802.11n devices. Also works great with older G products.
- Complies with IEEE 802.11g and 802.11b standards, and compatible with some IEEE 802.11n draft 2.0 features.
- DHCP Server capability to assign IP addresses automatically
- Denial of Service (DoS)
 prevention helps prevent Ping
 of Death, SYN Flood, Land
 Attack, and IP Spoofing
- Enhanced security management functions: Port Filtering, MAC and IP Address Filtering, DMZ Hosting, and NAT Technology



ıllııllı CISCO

Cisco Consumer Business Group

www.linksysbycisco.com/international

© 2009 Cisco Systems, Inc. All rights reserved. Cisco, the Cisco logo, Linksys, Network Magic and the Network Magic logo are trademarks or registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries. All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company.

Specifications

Model WAG120N

Standards WLAN: 802.11n draft 2.0, 802.11g, 802.11b

Ethernet: 802.3, 802.3u

ADSL: T1.413i2, G.992.1 (G.DMT), G.992.2 (G.Lite), G.992.3

(ADSL2), G.992.5 (ADSL2+) for Annex A, B, M, L, U-R2 for Annex B

Ports DSL, Ethernet (1-4), Power

Buttons On/Off, Reset, Wi-Fi Protected Setup™

LEDs Power, Ethernet (1-4), Security, Wireless, DSL, Internet

Cabling Type CAT5, RJ-11 (for Annex A), RJ-45 (for Annex B)

Antennas 2 Internal

Modulations 802.11b: CCK/QPSK, BPSK

802.11g: OFDM/BPSK, QPSK, 16-QAM, 64-QAM 802.11n: OFDM/BPSK, QPSK, 16-QAM, 64-QAM

Transmit Power 802.11b: 17,0 \pm 1,0 dBm

 $802.11g: 15,0 \pm 1,0 dBm$ $802.11n: 13,0 \pm 1,5 dBm$

Receive Sensitivity -80 dBm (typical) @ 11 Mbps

-70 dBm (typical) @ 54 Mbps -61 dBm (typical) @ 130 Mbps -61 dBm (typical) @ 270 Mbps

Antenna Gain 1,8 dBi

Security Features WPA2™/WPA™ Personal and Enterprise; 128, 64 bits WEP;

MAC Address Filtering; SPI Firewall

Environmental

Dimensions 202 x 34 x 160 mm

Weight 362 g Power 12VDC, 1A

Certification FCC, CE, Telepermit, K.21, UL, CB, Wi-Fi (802.11b/q),

WPA™, WPA2™, WMM, Wi-Fi Protected Setup™

Operating Temp. 0 to 40° C (32 to 104° F)

Storage Temp. -20° C to 70° C (-4 to 158° F)

Operating Humidity 10 to 85% Noncondensing

Storage Humidity 5 to 90% Noncondensing

Package Contents

- · Wireless-N Home ADSL2+ Modem Router
- Setup Software and User Guide on CD-ROM
- Ethernet Network Cable
- Telephone Cable (Annex A)
- Power Adapter

Minimum Requirements

- · Active ADSL Line and Account Information
- Internet Explorer 6, Safari 3 or Firefox 2 or Higher for Browser-Based Configuration
- CD or CD/DVD Drive
- Network Magic Basic Software requires up-to-date Windows XP, Vista, or Vista 64-bit Edition
- Setup Wizard also runs under Mac OS X 10.4 or higher

The maximum performance for wireless is derived from IEEE Standard 802.11 specifications. Actual performance can vary, including lower wireless network capacity, data throughput rate, range and coverage. Performance depends on many factors, conditions and variables, including distance from the access point, volume of network traffic, building materials and construction, operating system used, mix of wireless products used, interference and other adverse conditions.

Specifications are subject to change without notice.